



4000, 500, 6000 Fixed Picture WINDOW PERFORMANCE TABLE



Model	Style	VT	Metric U-Factor W/m ² .k	Imperial U-Factor ft ² .h	Imperial Value	R	SHGC	ER	Canada (Yes/No)	US Zones	NAF TEST RESULTS MAXIMUM SIZE TESTED
4000, 5000, 6000 Series Fixed Picture											
4020CLEAR	Fixed Picture	0.7	2.44	0.43	2.33	0.66	24				R-PG45, Size Tested (51 x 96)
4020CLEAR_GRIDS	Fixed Picture	0.63	2.44	0.43	2.33	0.6	21				R-PG45, Size Tested (51 x 96)
4020SOLR_GAIN	Fixed Picture	0.68	1.58	0.28	3.57	0.6	40		Y	N	R-PG45, Size Tested (51 x 96)
4020SOLR_GAIN_GRIDS	Fixed Picture	0.61	1.58	0.28	3.57	0.54	36		Y	N	R-PG45, Size Tested (51 x 96)
4020EVOLV	Fixed Picture	0.66	1.31	0.23	4.35	0.55	43		Y	N	R-PG45, Size Tested (51 x 96)
4020EVOLV_GRIDS	Fixed Picture	0.59	1.31	0.23	4.35	0.5	40		Y	N	R-PG45, Size Tested (51 x 96)
4020SOLR_SHIELD_PLUS_366	Fixed Picture	0.55	1.47	0.26	3.85	0.33	27			N, NC	R-PG45, Size Tested (51 x 96)
4020SOLR_SHIELD_PLUS_366_GRIDS	Fixed Picture	0.49	1.47	0.26	3.85	0.3	25			N, NC	R-PG45, Size Tested (51 x 96)
4020EVOLV_366_LOWE	Fixed Picture	0.54	1.23	0.22	4.55	0.23	26			N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020EVOLV_366_LOWE_GRIDS	Fixed Picture	0.48	1.23	0.22	4.55	0.21	25			N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020TRIPLE_CLEAR	Fixed Picture	0.64	1.65	0.29	3.45	0.6	38		Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_CLEAR_GRIDS	Fixed Picture	0.58	1.65	0.29	3.45	0.54	35		Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_GAIN_1LOWE	Fixed Picture	0.62	1.19	0.21	4.76	0.51	43		Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_GAIN_1LOWE_GRIDS	Fixed Picture	0.55	1.19	0.21	4.76	0.46	41		Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_GAIN_2LOWE	Fixed Picture	0.59	0.91	0.16	6.25	0.48	48		Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_GAIN_2LOWE_GRIDS	Fixed Picture	0.53	0.91	0.16	6.25	0.43	45		Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_GAIN_EVOLV	Fixed Picture	0.6	1.02	0.18	5.56	0.49	46		Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_GAIN_EVOLV_GRIDS	Fixed Picture	0.54	1.02	0.18	5.56	0.44	43		Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_SHIELD_366_LOWE	Fixed Picture	0.5	1.17	0.21	4.76	0.22	27		Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_SHIELD_366_LOWE_GRIDS	Fixed Picture	0.45	1.17	0.21	4.76	0.2	26		Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020TRIPLE_EVOLV_SOLR_SHIELD_366_LOWE	Fixed Picture	0.49	1.01	0.18	5.56	0.21	30		Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020TRIPLE_EVOLV_SOLR_SHIELD_366_LOWE_GRIDS	Fixed Picture	0.44	1.01	0.18	5.56	0.19	29		Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020_4MM_CLEAR	Fixed Picture	0.7	2.44	0.43	2.33	0.64	23				R-PG45, Size Tested (51 x 96)
4020_4MM_CLEAR_GRIDS	Fixed Picture	0.62	2.44	0.43	2.33	0.58	20				R-PG45, Size Tested (51 x 96)
4020_4MM_SOLR_GAIN	Fixed Picture	0.67	1.53	0.27	3.70	0.57	39		Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_SOLR_GAIN_GRIDS	Fixed Picture	0.6	1.53	0.27	3.70	0.51	36		Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_EVOLV	Fixed Picture	0.66	1.31	0.23	4.35	0.53	42		Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_EVOLV_GRIDS	Fixed Picture	0.59	1.31	0.23	4.35	0.48	39		Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_SOLR_SHIELD_PLUS_366	Fixed Picture	0.55	1.47	0.26	3.85	0.33	27			N, NC	R-PG45, Size Tested (51 x 96)
4020_4MM_SOLR_SHIELD_PLUS_366_GRIDS	Fixed Picture	0.49	1.47	0.26	3.85	0.3	25			N, NC	R-PG45, Size Tested (51 x 96)
4020_4MM_EVOLV_366_LOWE	Fixed Picture	0.53	1.22	0.22	4.55	0.23	26		Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020_4MM_EVOLV_366_LOWE_GRIDS	Fixed Picture	0.48	1.22	0.22	4.55	0.21	25		Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_CLEAR	Fixed Picture	0.63	1.70	0.3	3.33	0.58	36		Y		R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_CLEAR_GRIDS	Fixed Picture	0.57	1.70	0.3	3.33	0.52	32				R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_GAIN_1LOWE	Fixed Picture	0.61	1.25	0.22	4.55	0.49	41		Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_GAIN_1LOWE_GRIDS	Fixed Picture	0.55	1.25	0.22	4.55	0.44	38		Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_GAIN_2LOWE	Fixed Picture	0.59	0.97	0.17	5.88	0.46	45		Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_GAIN_2LOWE_GRIDS	Fixed Picture	0.53	0.97	0.17	5.88	0.42	43		Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_GAIN_EVOLV	Fixed Picture	0.6	1.08	0.19	5.26	0.47	43		Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_GAIN_EVOLV_GRIDS	Fixed Picture	0.53	1.14	0.2	5.00	0.43	40		Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_SHIELD_366_LOWE	Fixed Picture	0.5	1.19	0.21	4.76	0.22	26		Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_SHIELD_366_LOWE_GRIDS	Fixed Picture	0.45	1.23	0.22	4.55	0.2	24			N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_EVOLV_SOLR_SHIELD_366_LOWE	Fixed Picture	0.49	1.04	0.18	5.56	0.21	29		Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_EVOLV_SOLR_SHIELD_366_LOWE_GRIDS	Fixed Picture	0.44	1.07	0.19	5.26	0.19	27		Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)